



### SECTION B-B FOR SIDEWALKS WITH PARAPET

Scale: 1/2" = 1'-0"

#### Note:

All longitudinal bars are #5's and shall be placed continuously in the sidewalk from expansion opening to expansion opening in a simple span bridge and expansion opening to centerline of pier in a multispan bridge. Refer to BR-SS(6.48)-03-350.

#### Note C:

The constr. jt. between the sidewalk and the deck may vary slightly from the joint indicated.  
For exact details and location of the joint see "Superstructure" Sheet.

## RECESSED BACK WITH SIDEWALK

APPROVAL	
<i>E. S. Friedman</i>	DIRECTOR
OFFICE OF STRUCTURES	
DATE: 6/11/05	
REVISIONS	
SHA	FHWA

FHWA APPROVAL  
DATE:  

STATE OF MARYLAND  
DEPARTMENT OF TRANSPORTATION  
STATE HIGHWAY ADMINISTRATION  
OFFICE OF STRUCTURES

SUPPORT BRACKET FOR BRIDGE MOUNTED LIGHT POST  
WITH DUAL CONDUITS AND PARAPET WITH  
ARCHITECTURAL FINISH AND SIDEWALK

STANDARD NO. BR-SS(6.57)-05-359

SHEET 2 OF 2

SUPER-CONCRETE WORK